



**PB-31101-029A**  
Supersedes PB-31101-029


## **GE Renewal Parts**


*Use original equipment parts for reliability*


**PARTS BULLETIN**


**DRILLING MOTOR  
MODEL 5GE752ARB1A**

SEPTEMBER 9, 1992









(Representative Illustration)  
FIG. 2 (Cont'd.)



DRILLING MOTOR  
MODEL 5GE752ARB1A

PB-31101-029A  
Supersedes PB-31101-029

FIG. NO.	REF. NO.	PART NO.	QUANT. REQ. COL. A	DESCRIPTION
1	1	5GE752ARB1A	1	DRILLING MOTOR
1	2	4732368P1	2	+GASKET, 0.021 IN THK
1	3	6739891P1	1	BEARING CAP
1	4	N22P33048	8	BOLT, HEX HD, 5/8 IN-11, 3 IN LONG
1	5	41B537660P9	8	WASHER, FLAT, 0.725 IN ID, 1 IN OD
1	6	9949565G1	1	FRAME HEAD ASSEMBLY
1	7	481A560G1	1	FLASH RING
1	8	N22P29020B13	6	BOLT, HEX HD, 1/2 IN-13, 1 1/4 IN LONG
1	9	N509P2516	1	PIN, SPRING DOWEL, 1/4 IN DIA, 1 IN LONG
1	10	8864951P119	1	+ROLLER BEARING
1	11	334B761P1	1	BEARING CAP
1	12	949X47	1	RETAINING NUT WITH SET SCREW
1	13	41A239107P1	2	SCREW, HEX SOC HD, 1/2 IN-13, 3/4 IN LONG
1	14	8864951P167	1	+ROLLER BEARING
1	15	4713640P1	1	FLINGER
1	16	6744700P2	1	BEARING CAP, INNER
1	17	41C637314P1	1	*FRAME HEAD
1	18	4732906P1	2	+GASKET, 0.021 IN THICK
1	19	2739317P1	1	BEARING CAP
1	20	4732351P1	1	SLEEVE
1	21	N22P33056	8	BOLT, HEX HD, 5/8 IN-11, 3 1/2 IN LONG
1	22	41B537660P9	8	WASHER, FLAT, 0.725 IN ID, 1 IN OD
1	23	N22P39032	11	BOLT, HEX HD, 1 IN-8, 2 IN LONG
1	24	41B537660P21	11	WASHER, FLAT, 1.063 IN ID, 2 IN OD
1,2	25	41E903691G7	2	*EXCITING COIL
2	26	41E903691G8	2	*EXCITING COIL
1,2	27	41B537112G2	4	POLE PIECE, EXCITING COIL
1,2	28	41C637285G7	2	COIL WITH POLE PIECE, COMMUTATING
1,2	29	41C637285G8	2	COIL, COMMUTATING
2	30	41C637285G10	2	*COIL WITH POLE PIECE, COMMUTATING
2	31	41C637285G11	2	*COIL, COMMUTATING
1,2	32	N22P45060	12	BOLT, HEX HD, 1 1/4 IN-7, 3 3/4 IN LONG
1,2	33	41A239559P1	12	BOLT, HEX HD, 1 1/4 IN-12, 4 IN LONG
1,2	34	41B537660P22	24	WASHER, FLAT, 1.453 IN ID, 2.500 IN OD
2	35	41C636243G2	2	CABLE ASSEMBLY
2	36	41C636867G3	2	#CONNECTION STRAP
2	37	41C637268G1	1	CABLE ASSEMBLY
2	38	41C637268G2	1	CABLE ASSEMBLY
2	39	41D735504G3	1	CABLE ASSEMBLY
2	40	41D735504G5	1	CABLE ASSEMBLY

\* ADDED OR CHANGED SINCE LAST ISSUE.

# WELD OR BRAZE IN POSITION.

+ RECOMMEND CUSTOMER STOCK THIS PART.

FIG. NO.	REF. NO.	PART NO.	QUANT REQ. COL. A	DESCRIPTION
2	41	41C637269G2	1	#CONNECTION STRAP
2	42	41C637269G1	1	#CONNECTION STRAP
2	43	41C637269P1	1	CONNECTION STRAP
2	44	41C637269G3	1	CONNECTION STRAP
2	45	41C637269G4	1	CONNECTION STRAP
		DELETED	8	NOT USED
2	47	41C637261G1	1	CONNECTION STRAP, INSULATED
2	48	41C637261G5	1	CONNECTION STRAP, INSULATED
2	49	41C637261G2	1	CONNECTION STRAP, INSULATED
2	50	41D735504G7	1	SHUNT ASSEMBLY
2	51	41D735504G6	1	SHUNT ASSEMBLY
2	52	481A539P20	4	CABLE BUSHING, 1 1/2 IN ID, RUBBER
2	53	41A216775P1	AR	+SEALANT, 1/8 BY 3 3/4 IN, 10 FT ROLL
2	54	41A237748G1	2	GROUND STRAP
2	55	41A235215P1	2	HOSE CLAMP, 0.75 IN TO 1.75 IN ID
2	56	N22P33028	1	BOLT, HEX HD, 5/8 IN-11, 1 3/4 IN LONG
2	57	N22P33024	1	BOLT, HEX HD, 5/8 IN-11, 1 1/2 IN LONG
2	58	N405P47B13	2	LOCKWASHER, 5/8 IN
2	59	N213P33	2	NUT, HEX, JAM, 5/8 IN-11
2	60	N22P27028B13	6	BOLT, HEX HD, 7/16 IN-14, 1 3/4 IN LONG
2	61	N22P27024B13	4	BOLT, HEX HD, 7/16 IN-14, 1 1/2 IN LONG
2	62	N405P44B13	20	LOCKWASHER, 7/16 IN
2	63	4713845P1	3	*BOLTING PLATE
2	64	N22P27020B13	10	BOLT, HEX HD, 7/16 IN-14, 1 1/4 IN LONG
2	65	41A239176P443	AR	SILASTIC PUTTY
2	66	41A239176P133	AR	SILICONE TAPE, 0.015 IN THICK, 1 IN WIDE
2	67	41A239176P22	AR	GLASS TAPE, 0.007 IN THICK, 1 IN WIDE
2	68	41A239176P487	AR	VARNISH
2	69	41A239176P399	AR	CORD
2	70	41A231281P47	7	BRAZING STRIP
2	71	41A231281P46	8	BRAZING STRIP, 1 IN X 1 IN LONG
2	72	41A330300P2	AR	BRAZING ALLOY, 0.050 X 0.062 IN
2	73	499A918DBP20	4	CONNECTOR, 1.375 TO 1.625 IN DIA CABLE
		499A904CYP3	1	BUSHING, REDUCING, 3/4 IN X 1/4 IN
2	75	41A306142P5	4	LOCKNUT W/WATER TIGHT SEAL, 1 1/2 IN CONDUIT
		N5700P63	4	PIPE PLUG, 3/4 IN, CSK SQ HD
2	77	41A239663P2	4	PLUG
1	78	41B537963P1	12	*+CARBON BRUSH
1,2,3	79	41C632667G6	4	+BRUSH HOLDER ASSEMBLY
3	80	41B530659G2	12	PRESSURE ARM

\* ADDED OR CHANGED SINCE LAST ISSUE.  
# WELD OR BRAZE IN POSITION.  
+ RECOMMEND CUSTOMER STOCK THIS PART.

DRILLING MOTOR  
MODEL 5GE752ARB1A

PB-31101-029A  
Supersedes PB-31101-029

FIG. NO.	REF. NO.	PART NO.	QUANT REQ. COL. A	DESCRIPTION
3	81	41A231370P2	12	BUSHING, 1.063 IN LONG
3	82	186V831P1	8	SLEEVE
3	83	41A231378P2	4	PIN, 3/8 IN DIA, 6 5/8 IN LONG
3	84	N509P2548	8	PIN, SPRING DOWEL, 1/4 IN DIA, 3 IN LONG
3	85	N509P912	8	PIN, SPRING DOWEL, 3/32 IN DIA, 3/4 IN LONG
3	86	41A230733P7	8	BOLT W/WASHER, HEX HD SL, 5/16 IN-18, 3/4 IN LONG
3	87	41A231370P6	16	BUSHING, 0.575 IN LONG
3	88	41A330248P1	12	SPRING SEAT
3	89	41A233867G4	12	SPRING SEAT WITH PIN
3	90	41B537844G1	12	SPRING SET ASSEMBLY
3	91	41A233880P1	4	PIN, 7 7/16 IN LONG
3	92	41B535754G28	8	BRUSH HOLDER STUD, MOLDED (0.002 IN OVERSIZE)
3	93	41B535754G29	8	BRUSH HOLDER STUD, MOLDED (0.004 IN OVERSIZE)
3	94	41B535754G30	8	BRUSH HOLDER STUD, MOLDED (0.006 IN OVERSIZE)
3	95	41B535754G31	8	BRUSH HOLDER STUD, MOLDED (0.008 IN OVERSIZE)
1	96	2733755P7	4	SUPPORT, BRUSH HOLDER
1	97	N22P37052	4	BOLT, HEX HD, 7/8 IN-9, 3 1/4 IN LONG
1	98	41B537660P25	4	WASHER, FLAT, 0.968 IN ID, 1.375 IN OD
1	99	41D735773G1	1	*ARMATURE ASSEMBLY
1	100	41C636928G1	1	SHAFT WITH PLUG
1	101	8819420P1	2	PLUG, HEX SOC HD, 3/8 IN-24, 1 IN LONG
1	102	41B537605P4	1	*ARMATURE HEAD
1	103	41A239323G1	1	*PUNCHING, END
1	103A	41A330418G1	1	*PUNCHING, END
1	104	41B537164P1	553	PUNCHING, MAIN
1	105	41B537165P1	26	*PUNCHING, STEP BACK
1	105A	41B537165P2	14	*PUNCHING, STEP BACK
1	106	41B537889G2	1	COMMUTATOR, SEASONED
1	107	41B537080P1	1	*=TEFLON BAND (CONTINUOUS)
1	108	189V584P1	1	NUT
1	109	41D735370G5	1	*+REWIND KIT
1	110	41A330208P10	AR	WIRE, 0.072 IN DIA
1	111	41A239176P64	AR	GLASS TAPE, 0.014 IN THICK, 3/4 IN WIDE
1	112	41A232821P1	1	SLEEVE
1	113	2766829ADP24	AR	#BALANCE WEIGHT, 13 IN OD
1	114	2766829ADP26	AR	#BALANCE WEIGHT, 14 3/4 IN OD
1	115	41C636513G1	1	INSPECTION COVER, UPPER
1	116	41C636513P11	2	+GASKET, 9 3/4 IN LONG
1	117	41C636513P12	2	+GASKET, 11 1/4 IN LONG

\* ADDED OR CHANGED SINCE LAST ISSUE.

# WELD OR BRAZE IN POSITION.

+ RECOMMEND CUSTOMER STOCK THIS PART.

= ADDITIONAL MATERIAL IS REQUIRED TO INSTALL THE CONTINUOUS LOOP TEFLON BAND. SEE APPLICATION INSTRUCTIONS, GEK-76278.

FIG. NO.	REF. NO.	PART NO.	QUANT REQ. COL. A	DESCRIPTION
1	118	497A806P12	AR	+CEMENT
1	119	41D732878G4	1	INSPECTION COVER, LOWER
1	120	41D732878P7	2	+GASKET, 11 9/32 IN LONG
1	121	41D732878P8	2	+GASKET, 9 1/2 IN LONG
1	122	497A806P12	AR	+CEMENT
1	123	41A239914G1	1	INSPECTION COVER, HAND HOLE
1	124	41A239914P2	2	GASKET, NEOPRENE, 0.250 X 0.560 X 9.250 IN LONG
1	125	41A239914P3	2	GASKET, NEOPRENE, 0.250 X 0.560 X 8.120 IN LONG
1	126	497A806P12	AR	CEMENT
1	127	N22P29016B13	20	BOLT, HEX HD, 1/2 IN-13, 1 IN LONG
1	128	N405P45B13	20	LOCKWASHER, 1/2 IN
1	129	8855497P6	1	SPLASH GUARD
1	130	8855497P7	1	SPLASH GUARD
1	131	8855497P8	1	SPLASH GUARD
1	132	8855497P9	1	SPLASH GUARD
		41A237902P1	1	PLATE (WARNING - DO NOT OPEN WHILE -)

+ RECOMMEND CUSTOMER STOCK THIS PART.

- END OF PARTS BULLETIN -