



**Original Bushing Information**

**Original Bushing Manufacturer:** G.E.      **Mounting Position:**  
**Catalog Number:** 11B197BB  
**Voltage Class (kV):** 230      **BIL (kV):** 1050

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		1600	
230W1600UC (Amps)		1600	

**General Comments:**

**Replacement Information**

**ABB Style Number:** [230W1600UC](#) **Alternate ABB Style Number:**

**Review dimensional differences verifying critical dimensions to meet application requirements.**

**Notes/Comments:**

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
11B197BB	1050kV	26.75 in.	26.75 in.	59.5 in.	118.19 in.	12 in.	21 in.	12	1.25 slots in.	300 in.
230W1600UC	1050kV	26.75 in.	26.75 in.	59.546 in.	120.595 in.	12 in.	21 in.	12	1.25 in.	304 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
11B197BB	95 in.	16.875 in.	110.19 in.	101.19 in.	2.0-12 x 2.5	ansi/IEEE fig 3
230W1600UC	95.031 in.	16.875 in.	N/A	101.031 in.	2.000-12UN-2A, 2.625 USABLE THD x	IEEE fig 3 N/A

**Cable Adapter:** NONE  
**Flange Adapter:** NONE