



Original Bushing Information

Original Bushing Manufacturer: G.E. Mounting Position:
 Catalog Number: 11B414
 Voltage Class (kV): 138 BIL (kV): 650

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		2500	3000
138X2530AD (Amps)		2500	3000

General Comments:

Replacement Information

ABB Style Number: [138X2530AD](#) Alternate ABB Style Number:

Review dimensional differences verifying critical dimensions to meet application requirements.

Notes/Comments:

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
11B414	650kV	23 in.	23 in.	46.75 in.	56.06 in.	9.75 in.	14.25 in.	6	1.25 slots in.	103.8 in.
138X2530AD	650kV	23 in.	23 in.	46.734 in.	56.094 in.	9.75 in.	14.25 in.	6	1.25 in.	103.8 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
11B414	42.12 in.	N/A	N/A	48.12 in.	3.0-12 X 3.0	ANSI/IEEE FIG 2
138X2530AD	42.125 in.	9.5 in.	N/A	48.125 in.	3.000-12UN-2A x 12 UN-2A	(8) .500-13UN-2B tapped holes on 6.75 dia B.C. (8) .500-13 in.

Cable Adapter:

NONE

Flange Adapter:

NONE