



**Original Bushing Information**

**Original Bushing Manufacturer:** G.E.      **Mounting Position:**  
**Catalog Number:** 11B421BB  
**Voltage Class (kV):** 161      **BIL (kV):** 750

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		1200	1600
161W1216AK (Amps)		1200	1600

**General Comments:**

**Replacement Information**

**ABB Style Number:** 161W1216AK **Alternate ABB Style Number:**

**Review dimensional differences verifying critical dimensions to meet application requirements.**

**Notes/Comments:**

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
11B421BB	750kV	23 in.	23 in.	50.25 in.	74.3 in.	10.75 in.	15.75 in.	8	1.25 slots in.	132 in.
161W1216AK	750kV	23 in.	23 in.	50.297 in.	74.781 in.	10.75 in.	15.75 in.	8	1.25 in.	131.938 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
11B421BB	50.3 in.	11.375 in.	N/A	56.97 in.	1.5-12x2.0	ansi/IEEE fig 2
161W1216AK	50.28 in.	11.375 in.	N/A	56.28 in.	1.500-12x2.125, SP x 12 UN-2A	(4) .375-16UN-2B tapped holes on 3.75 B.C./ (8) .500-12UN-2B tapped on 6.75 B.C.