



Original Bushing Information

Original Bushing Manufacturer: G.E. **Mounting Position:**

Catalog Number: 11B424BB

Voltage Class (kV): 161 **BIL (kV):** 750

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		2500	3000
161W2530AD (Amps)		2500	3000

General Comments:

Replacement Information

ABB Style Number: [161W2530AD](#) **Alternate ABB Style Number:**

Review dimensional differences verifying critical dimensions to meet application requirements.

Notes/Comments:

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
11B424BB	750kV	23 in.	23 in.	50.25 in.	73.81 in.	10.75 in.	15.75 in.	8	1.25 slots in.	129.6 in.
161W2530AD	750kV	23 in.	23 in.	50.297 in.	74.703 in.	10.75 in.	15.75 in.	8	1.25 in.	131.938 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
11B424BB	50.31 in.	12.125 in.	in.	56.31 in.	3.0-12 x 3	ansi/IEEE fig 3
161W2530AD	50.28 in.	11.375 in.	N/A	56.28 in.	3.000 - 12UN- 2A 3.00 Usable Thread, SP	(8) .5-13 holes on 6.75 bc / (4) .375-16 holes on 3.75 bc