



**Original Bushing Information**

**Original Bushing Manufacturer:** G.E.      **Mounting Position:**  
**Catalog Number:** 11B450BB  
**Voltage Class (kV):** 138      **BIL (kV):** 650

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)	800		
138Z0800XA (Amps)	800		

**General Comments:**

**Replacement Information**

**ABB Style Number:** [138Z0800XA](#) **Alternate ABB Style Number:**

**Review dimensional differences verifying critical dimensions to meet application requirements.**

**Notes/Comments:**

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
11B450BB	650kV	23 in.	23 in.	47.12 in.	68.4 in.	9.75 in.	14.25 in.	6	1.25 slots in.	125.5 in.
138Z0800XA	650kV	26.875 in.	23 in.	47.188 in.	68.531 in.	7.725 in.	14.25 in.	6	1.25 in.	150.375 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
11B450BB	50.89 in.	9.5 in.	63.234 in.	58.89 in.	1.5-12x2.0	1.625 id tube
138Z0800XA	51.031 in.	8.000 in.	58.522 in.	54.781 in.	1.500-12UN-2A, 2.125 USABLE THD, SP x	1.625 id tube N/A

**Cable Adapter:** NONE

**Flange Adapter:** NONE