



**Original Bushing Information**

**Original Bushing Manufacturer:** G.E.    **Mounting Position:**  
**Catalog Number:** 11B767  
**Voltage Class (kV):** 345    **BIL (kV):** 1175

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		1600	
362X1600WD (Amps)		1600	

**General Comments:**

**Replacement Information**

**ABB Style Number:** [362X1600WD](#)    **Alternate ABB Style Number:**

**Review dimensional differences verifying critical dimensions to meet application requirements.**

**Notes/Comments:**

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
11B767	1175kV	23 in.	23 in.	62.63 in.	128.12 in.	15.12 in.	21 in.	12	1.250 in.	240 in.
362X1600WD	1175kV	26.25 in.	26.25 in.	62.593 in.	128.172 in.	14.875 in.	21 in.	12	1.25 in.	262.125 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
11B767	101.94 in.	16.875 in.	NA in.	107.94 in.	2-12x2.5	ansi/IEEE fig 3
362X1600WD	101.984 in.	12.50 in.	N/A	107.984 in.	2.0-12x2.5 x	(8) .5-13 holes on 6.75 bc N/A

**Cable Adapter:**

NONE

**Flange Adapter:**

NONE