



Original Bushing Information

Original Bushing Manufacturer: G.E.      Mounting Position: Vertical  
Catalog Number: 11B770BB  
Voltage Class (kV): 345      BIL (kV): 1050

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)	800		
362W0800UR (Amps)	800		

General Comments:

Replacement Information

ABB Style Number: 362W0800UR Alternate ABB Style Number:

Review dimensional differences verifying critical dimensions to meet application requirements.

Notes/Comments: Cable Adapter required Note Difference in Tube ID, check cable diameter for fit.

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
11B770BB	1050kV	23 in.	23 in.	60.375 in.	130 in.	14.875 in.	21 in.	12	1.25 in.	N/A
362W0800UR	1050kV	23 in.	23 in.	59.813 in.	132.844 in.	14.875 in.	21 in.	12	1.25 in.	262.125 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
11B770BB	102 in.	16.875 in.	117.1 in.	108 in.	1.5-12 x 2.125 SP	2.250 tube ID
362W0800UR	101.969 in.	16.875 in.	129.406 in.	107.969 in.	1.500-12UN-2A x 2.125 USABLE THREAD, SP x	2.0 id tube N/A

Cable Adapter: 1ZUA264308-BAD  
Flange Adapter: NONE