



Original Bushing Information

Original Bushing Manufacturer: G.E. **Mounting Position:** Vertical
Catalog Number: 11B773
Voltage Class (kV): 500 **BIL (kV):** 1675

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		2000	
550W2000XC (Amps)		2000	

General Comments: Shield included in "L" Dimension - OD of shield is 16.25

Replacement Information

ABB Style Number: 550W2000XC **Alternate ABB Style Number:**

Review dimensional differences verifying critical dimensions to meet application requirements.

Notes/Comments:

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
11B773	1675kV	31.5 in.	31.5 in.	103.812 in.	207.562 in.	23 in.	31 in.	16	1.25 in.	321 in.
550W2000XC	1675kV	31.5 in.	31.5 in.	104.219 in.	208.312 in.	23 in.	31 in.	16	1.25 in.	456.25 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
11B773	170 in.	23 in.	N/A	177.5 in.	2.0-12x2.5	(4) .562 Holes / Blade on 1.75" square
550W2000XC	170.031 in.	23 in.	N/A	177.531 in.	2.0-12x2.5, SP x	(1) Blade, (4) .562 DIA HOLES, W/SHIELD N/A

Cable Adapter:

NONE

Flange Adapter:

NONE