



Original Bushing Information

Original Bushing Manufacturer: G.E. **Mounting Position:** Vertical
Catalog Number: 11B777BB
Voltage Class (kV): 500 **BIL (kV):** 1425

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		2000	
550W2000UZ (Amps)		2000	

General Comments: Type "U" Dwg. # 3946B966

Replacement Information

ABB Style Number: [550W2000UZ](#) **Alternate ABB Style Number:** [550X2000UZ](#)

Review dimensional differences verifying critical dimensions to meet application requirements.

Notes/Comments:

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
11B777BB	1425kV	26.75 in.	26.75 in.	86.688 in.	191.375 in.	23 in.	31 in.	16	1.125 in.	361 in.
550W2000UZ	1425kV	26.75 in.	26.75 in.	86.719 in.	191.421 in.	23 in.	31 in.	16	1.125 in.	402 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
11B777BB	153.062 in.	23 in.	N/A in.	160.563 in.	2.0-12x2.5, SP	(4) .50-13 on 7.0 & 10.5 BC
550W2000UZ	153.156 in.	23.00 in.	N/A	160.656 in.	2.0-12UN-2A, 2.500 USABLE THD x	(4) .50-13 on 7.0 B.C., (4) .50-13 on 10.5 B.C. N/A

Cable Adapter:

NONE

Flange Adapter:

NONE